

## SURE TREAD NON-SLIP-GRIT COATING

**SURE TREAD** is a non-slip coating that cures quickly to a durable soft grit finish. For indoor and outdoor use on tile, wood, concrete, aluminum, steel, fiberglass and virtually any surface where **SURE TREAD** traction is required. **SURE TREAD** is easy to apply and can help satisfy OSHA requirements. Help reduce slipping, falling and costly accidents by making **SURE TREAD** part of your safety program.

### GREAT FOR THESE APPLICATIONS:

Public restrooms, stairs, ladders, loading docks, high traffic areas, ramps, entry ways, emergency exits, diving boards, marine applications, pool decks, bathtubs, showers, roof hatch ladders, around equipment and machinery warehouse paths or where hazardous slippery conditions exist.

### DIRECTIONS:

Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use **SURE TREAD** when can is between 50°F and 90°F (10°C and 32°C). Shake **SURE TREAD** at least one minute after rattle is heard and occasionally during use. Spray **SURE TREAD** with steady even strokes at a distance of 6 to 10 inches (15 to 25cm). Several light coats give a better finish than one heavy coat. **SURE TREAD** is tack free in 60 minutes and fully cured in 24 hours. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other object into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion. To clear sprayhead for future use, turn **SURE TREAD** upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

Product Code: 2090-A  
TO REORDER CALL: (281) 647-9700 or  
1-800-295-BETA

**BETA TECHNOLOGY, INC.**  
Corporate Headquarters  
P.O. Box 218686  
Houston, TX 77218-8686

Exclusively for Industrial & Institutional Use



# SURE TREAD

## CLEAR NON-SLIP-GRIT COATING

- Slip Resistant
- For Indoor/Outdoor Use
- Starts Drying Immediately
- Specially Designed Soft Grit
- Made with Durable Epoxy
- Bonds with Virtually Any Surface

**DANGER:**  
EXTREMELY FLAMMABLE LIQUID AND VAPOR  
VAPORS MAY CAUSE FLASH FIRE  
CONTENTS UNDER PRESSURE  
READ OTHER CAUTIONS ON SIDE PANEL PRIOR TO USE  
NET WT. 12 OZ. (340 Grams)

### DANGER:

Acetone 57-64-1, Propane 74-98-6, Xylene 1330-20-7, N-Butane 106-97-8, Methyl Isobutyl Ketone 108-10-1, Ethyl Benzene 100-41-4, PM Acetate 108-65-6, Calcium Carbonate 1317-65-3, OTHER INGREDIENTS: \*Contents Partially Unknown, Epoxy Resin.

**EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR HARMFUL. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM. CAUSING DIZZINESS, HEADACHE OR NAUSEA. CAUSES EYE, SKIN, NOSE AND THROAT IRRITATION. Do not puncture or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F (49°C). NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Vapors may ignite explosively. Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe dust, vapors or spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA approved) or leave the area. Close container after each use. Avoid contact with eyes, skin and clothing. WARNING: This product contains a chemical known to the State of California to cause cancer.**

### FIRST AID:

If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water.

**HMS RATING:** Health: 1; Flammability: 4; Reactivity: 3; Personal Protection: B.

Slip Resistant Coatings (SRC)

do not exceed 80% VOC or 2.45 MIB

**KEEP OUT OF REACH OF CHILDREN**

For further information,

consult Material Safety Data Sheet.

