


EXCLUSIVELY FOR INDUSTRIAL & INSTITUTIONAL USE



PRO-VOLT

ELECTRICAL WATERPROOFING Spray

- Dries Clear • Flexible • Fast Drying
- Improves Dielectric Protection
- Enhances Conductivity
- Labor Saving Technology
- Protects Against Corrosion
- Creates Moisture Shield
- All-Weather Protection



NET WT.
11 OZ.

**CAUTION: EXTREMELY FLAMMABLE
VAPOR HARMFUL.
CONTENTS UNDER PRESSURE
KEEP OUT OF REACH OF CHILDREN
See Side Panel for Additional Cautions**

PRO-VOLT ELECTRICAL WATERPROOFING SPRAY

Pro-Volt is a revolutionary clear electrical waterproofing spray. Developed to protect all types of electrical contacts and connections. This product will conform to virtually any type of surface.

GREAT FOR USE ON

Electrical Boxes
Circuit Boards
Wiring • Cable Connections
Junction Boxes • Lighting
Electrical Panels
Conduit Joints
Exposed Contacts
Motors, etc.

Product Code: 2562-A

To Reorder Call (281) 647-9700 or
1-800-295-BETA

BETA TECHNOLOGY
CORPORATE HEADQUARTERS
P.O. BOX 218686
HOUSTON, TX 77218

DIRECTIONS

Remove plastic cap. Shake can for 30 to 40 seconds. Surface should be clean and dry before application. Spray in short sweeping strokes until desired coverage is achieved. Allow surface to dry for 15 minutes before use. To improve above 300 volt dielectric protection (4 milwatt), additional applications can be made. Clean up with solvent.

Turn can upside down after use and spray to clear nozzle.

DO NOT APPLY TO ENERGIZED EQUIPMENT OR LIVE HIGH VOLTAGE CONNECTIONS.

CAUTION:

Extremely Flammable. Contents under pressure. Keep out of the reach of children. Vapor harmful. Avoid breathing of vapors or mist. Avoid contact with skin and eyes. Do not apply to energized equipment. Do not use near fire, sparks or open flame. Do not puncture or incinerate container. Exposure to temperatures above 120°F may cause bursting.

WARNING: This product contains chemical(s) known to the State of California to cause cancer.

CONTAINS AROMATIC HYDROCARBON ALIPHATIC HYDROCARBON ACETONE XYLENE

VOC: CCP 1.5

HMS CODES: Health - 1;
Flammability - 3; Reactivity - 0,
Personal - A

M33844