

**CABLELOCITY O.G.
CABLE, CHAIN, & OPEN
GEAR LUBRICANT**

CABLELOCITY O.G. is a cable, chain and open gear lubricant. On cable, chain and wire rope it immediately starts to penetrate the inner core of the cable and wire rope to completely coat and protect. On open gears it instantly coats the surface with a durable protective film. Coats uniformly under high or low speed conditions. This unique product prevents sling out and strings out to coat gears and chains while mating components touch and separate during operations. CABLELOCITY O.G. is impervious to moisture because it is water insoluble. The optimum operating range is from 20° to 175°F.

**GREAT FOR THESE
APPLICATIONS**

Cable	Chain
Wire Rope	Drag Lines
Open Gears	Sprockets
Slides	Winches
Etc.	

DIRECTIONS

Shake well before using. Hold at least 6" from surface to be lubricated. Initially spray an even coating. Start up equipment and run to transfer product over all operating surfaces. Spray a light second coat to assure complete coverage. Reapply as required by working conditions.

Product Code: 2580-A

To Reorder Call (281) 647-9700
or 1-800-295-BETA

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
P.O. BOX 218686 • HOUSTON, TX 77218

EXCLUSIVELY FOR INDUSTRIAL & INSTITUTIONAL USE



**CABLELOCITY™
O.G.**

**CABLE, CHAIN &
OPEN GEAR LUBRICANT**



- *Eliminates Friction • Heavy Load Protection*
- *Repels Moisture • Guards Against Rust*
- *Withstands Extreme Pressure*
- *Provides Total Saturation*
- *Minimizes Dust Attraction • Sprays Thin – Sets Thick*
- *Fortified with Unique Adhesive and Cohesive Agents*

**NET WT.
12 OZ.**

**DANGER:
EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.**

CLEAN UP TIPS

Invert can and spray until the nozzle is clear.

DANGER

Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces.

–No smoking. Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

HMIS CODES: Health – 1; Flammability – 3;
Reactivity – 0; Personal – B