

EXCLUSIVELY FOR INDUSTRIAL & INSTITUTIONAL USE

**KOOL TOOL
FOAMING
PENETRATING &
CUTTING OIL**

KOOL TOOL is designed to be used on farm equipment, sports equipment, industrial equipment, marine and auto equipment. This fast penetrating product lubricates, displaces moisture, frees sticking parts, stops squeaks, stops rust and corrosion and provides long lasting protection.

DIRECTIONS

Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Spray liberally. Reapply periodically as required.

Product Code: 2880-A

To Reorder Call (281) 647-9700
or 1-800-295-BETA

BETA TECHNOLOGY, INC.
CORPORATE
HEADQUARTERS
P.O. BOX 218686
HOUSTON, TX 77218



**KOOL
TOOL**

**FOAMING
PENETRATING &
CUTTING OIL**

- *Multi Purpose Lubricant*
- *Frees Sticking Parts*
- *Stops Squeaks*
- *Seeks Friction*

**NET WT.
16 OZ.**

DANGER:
EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

DANGER

Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes eye irritation. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



HMS CODES:
Health - 1;
Flammability - 2;
Reactivity - 0;
Personal - A