



(281) 647-9700
or 1-800-295-BETA

Product Code: 2300

REMOVE GEL PAINT, GRAFFITI, VARNISH REMOVER

- USDA AUTHORIZED • NON-FLAMMABLE
- CLINGS TO VERTICAL SURFACES • WASHES OFF WITH WATER
- SAFE ON METAL, BRICK, TILE & CERAMIC SURFACES

FOR USE IN

- FACTORIES • PAINT SHOPS • HOSPITALS •
- MUNICIPALITIES • APARTMENTS • HOUSING AUTHORITIES •
- GARAGES • SCHOOL DISTRICTS •

DIRECTIONS

Pre-clean accumulations of dirt and grease with a heavy duty detergent. Allow to dry. Apply undiluted compound in a full heavy coat. Allow to stand until paint film is thoroughly wrinkled. On floors the used stripper may be squeegeed to the next area and reused until action completely stops. Add fresh material as needed. Stripped surfaces should be washed with detergent and water, particularly before repainting.

BETA DATA

FLASH POINT: None
VISCOSITY: Very Thick
COLOR: Clear to Slightly Hazy
SPECIFIC GRAVITY: 1.20
TOXICITY: 25 ppm OSHA PEL
DETERGENCY: Strong
STORAGE STABILITY: 1 year+
COLD STABILITY: 0° F
ODOR: Strong Chlorinated Solvent

WETTING ABILITY: Excellent
BOILING POINT: 104°F
SOLUBILITY IN WATER: Emulsifies
PHOSPHATES: None
BIODEGRADABILITY: No
pH: N/A
% VOLATILE BY VOLUME: 97.3+
EVAPORATION RATE: Fast
FORM: Solvent Base Liquid

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218