



(281) 647-9700
or 1-800-295-BETA

Product Code: 2520-A

PTFE GUARD

MICROSCOPIC DRY LUBRICANT

- EXCELLENT FILM-FORMING PROPERTIES • CONTAINS HIGH GRADE PTFE
- SUPER MOLD RELEASE AGENT • OPERATING RANGE -100°F – +500°F
 - UNIQUE FRICTION REDUCING POWDER SPRAY
 - TOUGH ULTRA DURABLE ANTI STICK COATING
- RESISTS WASH OFF FROM MOISTURE AND MOST SOLVENTS

GREAT FOR USE ON

- LOCKS • HINGES • SPRINGS
- CHAINS • SLIDES • DRAWERS • PULLEYS
- SAW BLADES • CUTTING TABLES

DIRECTIONS

Shake can vigorously, rattling agitator ball for a minimum of 1 full minute. Surface to be treated must be clean and dry. Hold container 5 to 10 inches from surface and spray a thin film over area.

BETA DATA

FLASH POINT:	<20°F TCC	WETTING ABILITY:	Saturates
PROPELLANT:	Hydrocarbon	FLAME EXTENSION:	>18"
COLOR:	Hazy White	SOLUBILITY IN WATER:	Slight
SPECIFIC GRAVITY:	0.78	PHOSPHATES:	None
TOXICITY:	400 ppm OSHA TLV	BIODEGRADABILITY:	No
DETERGENCY:	None	pH:	N/A
STORAGE STABILITY:	1 year	% VOLATILE BY VOLUME:	95+
COLD STABILITY:	0°F	EVAPORATION RATE:	Fast
ODOR:	Mild Petroleum	FORM:	Solvent Based Aerosol

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218