



TO REORDER CALL:
(281) 647-9700
or
1-800-295-BETA

Product Code:
2560-A

MAXI-GLIDE

Penetrating Gel Lubricant With PTFE

- SUPERIOR PENETRATING PERFORMANCE
- EXTREME WEATHER DURABILITY -30°F TO +500°F
- SETS TO A CLEAR, TACKY GEL
- PREVENTS RUST AND CORROSION
- IMPERVIOUS TO WATER
- LEAVES A MOISTURE-RESISTANT FILM

FOR USE ON

Wire Rope, Hinges, Sprockets, Rings, Seals, Bearings, Bushings, Gears, Slides, Valves, Pistons, Sleeves, And Pintle, Detachable Silent Roller And Block Chains, Windows, Doors, Pulleys, Rollers, Winches, Or Virtually Any Moving Part.

DIRECTIONS

Shake well before using. Remove cap and rotate actuator until orifice is pointed toward mark on valve cup. Spray holding can 12 to 14 inches away from surface to be treated. For hard to reach areas, insert extension tube into actuator orifice.

BETA DATA

FLASH POINT:	< 5°F (T.O.C.)	SOLUBILITY IN WATER:	Negligible
COLOR:	White, viscous liquid	ODOR:	solvent odor
PROPELLANT:	Carbon Dioxide	BIODEGRADABILITY:	Not Determined
STORAGE STABILITY:	1 yr. +	EVAPORATION RATE:	Not Determined
SPECIFIC GRAVITY:	0.757	FORM:	White, viscous liquid
STABILITY:	Material Stable	% VOLATILE BY WEIGHT:	~75%

BETA TECHNOLOGY, INC.

CORPORATE HEADQUARTERS
P.O. Box 218686 • Houston, TX 77218-8686