



TO REORDER CALL:
(281) 647-9700
or
1-800-295-BETA

Product Code:
2850-A

MEGA STEEL

LIQUID STAINLESS STEEL COATING

- STARTS TO DRY IN MINUTES
- TEMPERATURE RESISTANT TO 400°F
- RESISTS OXIDATION • SATIN SHEEN FINISH
- ENHANCED WITH POLY "BETA" RESIN CREATING AN IMPENETRABLE COATING
- CONTAINS STAINLESS STEEL 100% PURE PIGMENT 316L
- INDOOR / OUTDOOR USE • LONG LASTING

FOR USE IN

- INSTITUTIONAL KITCHENS • REFINERIES • HOSPITALS
- SCHOOL DISTRICTS • MUNICIPALITIES • OIL FIELD EQUIPMENT
- OUTDOOR EQUIPMENT • CHEMICAL PROCESSING EQUIPMENT
- VEHICLE REPAIR • OVENS • HEAT EXCHANGERS • MUFFLERS
- STEAM PIPES • BOILERS • PLUMBING • FIRE HYDRANTS

DIRECTIONS

PREPARATION PRIOR TO USE: Surface should be clean from dirt, oil, paint, rust, scale, corrosion, or wax prior to use. Shake **MEGA STEEL** vigorously until ball rattles freely. Shake for an additional 30 seconds for ideal mixture. Occasionally shake during use. Position **MEGA STEEL** 10 to 12 inches from surface area. Spray in a sweeping motion. For ideal results, spray several thin coats. **ATTENTION:** To prevent clogging, after each use turn **MEGA STEEL** upside down and spray a couple of short bursts to clear spray nozzle.

BETA DATA

FLASH POINT:	-2°F
COLOR:	Satin Stainless Steel
PROPELLANT:	Propane / N-Butane
STORAGE STABILITY:	1 yr. +
SPECIFIC GRAVITY:	0.77 - 0.90
COLD STABILITY:	Good

SOLUBILITY IN WATER:	Negligible
ODOR:	Solvent
BIODEGRADABILITY:	No
EVAPORATION RATE:	Unknown
FORM:	Silver Grey Liquid
% VOLATILE BY VOLUME:	Approx. 58

BETA TECHNOLOGY, INC.

CORPORATE HEADQUARTERS

P.O. Box 218686 • Houston, TX 77218-8686