



To Reorder Call (281) 647-9700  
or 1-800-295-BETA

Product Code: 7400-A

# ULTRA-SLIDE

## High Viscosity Silicone Lubricant

- UP TO 400°F
- 28,000 VOLT DIELECTRIC STRENGTH
- NON-STAINING
- PREVENTS STICKING
- MEETS FDA GUIDELINES
- ZERO FLASHPOINT
- IMPERVIOUS TO MOISTURE
- USDA AUTHORIZED (H-1 RATING)

### FOR USE IN

- HOTELS • HOSPITALS • MUNICIPALITIES • SCHOOL DISTRICTS •
- OUTDOOR EQUIPMENT • GOLF COURSES • CEMETERIES •
- AUTOMOTIVE DEPARTMENTS • MARINE APPLICATIONS •
- REFINERIES • PLACES OF WORSHIP • RESTAURANTS •
- FOOD PROCESSING PLANTS • NURSING HOMES •
- APARTMENTS • OFFICE BUILDINGS • MACHINE SHOPS •

### DIRECTIONS

Clean the surface thoroughly. Spray a light coating in a sweeping motion. Repeat the process if necessary. Work the part back and forth to ensure complete coverage.

### BETA DATA

<b>FLASH POINT:</b>	None	<b>WETTING ABILITY:</b>	Saturates
<b>FLAME EXTENSION:</b>	None	<b>PROPELLANT:</b>	CO2
<b>COLOR:</b>	Clear	<b>SOLUBILITY IN WATER:</b>	0%
<b>SPECIFIC GRAVITY:</b>	1.46	<b>PHOSPHATES:</b>	None
<b>TOXICITY:</b>	25 ppm OSHA TLV	<b>BIODEGRADABILITY:</b>	No
<b>DETERGENCY:</b>	None	<b>pH:</b>	N/A
<b>STORAGE STABILITY:</b>	1 year +	<b>% VOLATILE BY VOLUME:</b>	95
<b>COLD STABILITY:</b>	0°F	<b>EVAPORATION RATE:</b>	Slow
<b>ODOR:</b>	Chlorinated Solvent	<b>FORM:</b>	Solvent Base Aerosol

**BETA TECHNOLOGY, INC.**  
**CORPORATE HEADQUARTERS**  
**HOUSTON, TX 77218**