

**A.S.L.-2200™**  
**GRAPHITE BASED ANTI-SEIZE LUBRICANT**

An industrial grade lubricant and anti-seize compound developed to be used on various types of equipment, machines, fasteners, and fittings. A.S.L.-2200 has tremendous temperature and pressure ratings to withstand virtually any industrial application. Use in both high and low speed applications. This product resists acids and alkalis.

**GREAT FOR USE ON**

- Bolts • Nuts • Press Fit Unions • Bushings • Gaskets •
- Screws • Spark Plugs • Valves • Stainless Steel • Nickel •
- Ferrous & Non Ferrous Metals • Manifolds • Pipe Threads •
- Flanges • Threaded Fittings • Castings • Forming Dies •
- Packing Unions • Lug Nuts • Thread Bolts • Drive Chains •
- Pulleys • Fuel Injectors • Jibs • Hydraulic Fittings • Shafts •
- Worm Gears • Roller Assemblies • Caters • Stud Bolts •
- Thrust, Plain & Slide Bearings • Pump Sub Assemblies •
- Pitch Adjuster on Plows • Etc. •

EXCLUSIVELY FOR INDUSTRIAL & INSTITUTIONAL USE



**Saltwater  
Safe**

**A.S.L.-2200™**

**Graphite Based Anti-Seize Lubricant**

- *Extreme Pressure Safe* • *Non-Melt Formula*
- *Seals and Lubricates* • *Completely Impervious to Water*
- *Prevents Seizing, Galling or Fretting*
- *Industrial Temperature Ratings from -30° to 2200°F+*

**NET CONTENTS: 1 LB**

**CAUTION:**

**KEEP OUT OF REACH OF CHILDREN**  
**See Additional Cautions on Back Panel**

**DIRECTIONS FOR USE**

Clean surface thoroughly with Beta-50. Brush on a complete coating over the surface. Complete assembly and wipe off the excess material. NLGI Rating #2.

**CAUTION**

A.S.L.-2200 contains a petroleum based carrier, not to be used on oxygen lines. Keep out of reach of children.

HMIS Codes: Health - 1, Flammability - 0, Reactivity - 1, Personal - A.

Product Code 2150

To Reorder call 1-800-295-BETA or  
281-647-9700

**BETA TECHNOLOGY, INC.**  
**CORPORATE HEADQUARTERS**  
**P.O. BOX 218686 • HOUSTON, TX 77218**