

EXCLUSIVELY FOR INDUSTRIAL & INSTITUTIONAL USE

METAL KOTE
CLEAR COAT PROTECTANT FILM

Metal Kote is a clear coat protectant film for use on industrial metal applications. Protects metal parts from harsh corrosive elements. Ideal for short and long term storage applications. Metal Kote is a necessity for protecting equipment while in transit domestically or internationally. Displaces moisture to allow for a durable molecular bond for total parts protection.

GREAT FOR USE ON

Castings • Pipe • Cables • Dies • Tools
Valves • Stamped Metal Parts • Hoists
Threads • Housing • Winches • Rigging
Pulleys • Meets Mil Spec C-16173D,
Grade 4 & C83933A

DIRECTIONS

Clean parts of any dirt, soil, rust or scale prior to applying Metal Kote.

Shake the can well prior to spraying. Hold can 8 to 10 inches away from application point. Apply in a slow, steady sweeping spray. Saturate surface completely with product. For ultra harsh environments, apply a second coat after 5 minutes.

Total set up and cure time – two hours.

When coating is hard, it is ready to be handled.


<u>Coating Thickness</u>	<u>Outdoor Storage</u>	<u>Indoor Storage</u>
2 & 3 mil	1 year	Indefinite
5 & 6 mil	2 years	Indefinite

To remove coating, wash treated part with Beta-52. Once cleaned, parts are ready to be painted.

USDA Authorized for use in Federally Inspected Meat and Poultry Plants



METAL KOTE



Clear Coat Protectant Film

- **Prevents Corrosion** • **Mil Spec Grade**
- **Paintable** • **Flexible** • **Weldable**
- **Non-Crack or Peel Formula**
- **USDA Authorized** • **Indoor/Outdoor Use**

NET WT.
12.5 OZ.

ANGER:

EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE;
MAY EXPLODE IF HEATED.

DANGER

Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Keep away from heat, sparks, open flames, and hot surfaces. –No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.

HMS CODES: Health – 1; Flammability – 3; Reactivity – 1; Personal – B

Product Code: 2250-A
To Reorder Call (281) 647-9700 or
1-800-295-BETA

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
P.O. BOX 218686
HOUSTON, TX 77218



600002680