

**M.I.G.
MAXIMUM IMPACT GREASE**

M.I.G. performs up to 55 Timken load. Temperature rating up to 500°F. Contains unique corrosion and rust inhibitors. Enhanced with HM-1000 additive for maximum impact protection.

USE IN: Fifth Wheels, Back Hoes, Cranes, Car boxes, Universal Joints, Throw-out Bearings, Bull Gears, Bearings, Conveyors, Front End Loaders, King Pins, Transmissions, Spindles, Pillow Block Bearings, Overhead Crains, Tow Motors, Chains and Open Gears.

Product Code: 7020

To Reorder Call (281) 647-9700 or
1-800-295-BETA

**BETA TECHNOLOGY
CORPORATE HEADQUARTERS
HOUSTON, TX 77084**

EXCLUSIVELY FOR INDUSTRIAL & INSTITUTIONAL USE



**M.I.G.
MAXIMUM IMPACT GREASE
MAXIMUM**

- *Pound Out Protection* •
- *Water resistance* • *Weather Protection* •
- *Staying Power* • *Splatter Protection* •
- *Pressure Protection* •

• *Enhanced with HM-1000 for Maximum Impact Protection*

CAUTION:
KEEP OUT OF REACH OF CHILDREN
See Cautions on Side Panel

DIRECTIONS

Read directions on grease gun for loading. Follow arrows on label for proper tube placement in equipment. Make sure to pump out all old grease before applying Beta Technology's M.I.G.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin wash with soap and water. For ingestion of more than 8 ounces contact physician.