

# ***SLICK WILLY***

*SLICK WILLY* grease is designed to handle 65 lb. Timken load. The excellent water resistance and harsh environment features allow *SLICK WILLY grease* to have numerous uses in the industrial field. The extreme pressure properties make the building of mud motors (rotors and stators) extremely easy when measurements are tight.

## **APPLICATIONS**

- Bearings (Roller, Ball and Journal)
- Extreme Pressure Sliding
- Oilfield
- Industrial Applications
- Elevators
- Refineries
- Rolling Stock
- Harsh Environments
- Plunger Packing Lubrication

**FOR INDUSTRIAL USE ONLY**



# ***SLICK WILLY***

**The Ultimate Water – Resistant Grease  
(Calcium Sulfonate Complex)**

**BETA TECHNOLOGY, INC.  
CORPORATE HEADQUARTERS  
P.O. BOX 218686  
HOUSTON, TX 77218-8686**

**To re-order call  
281-647-9700 or 800-295-BETA**

**Product Code - 7075-40**

## **DIRECTIONS**

Read and follow the directions as listed on all grease guns, pneumatic grease gun equipment or automated greasing equipment. Old grease must be pumped or pushed out when Slick Willy Grease is injected to any equipment

## **PROPERTIES**

- Excellent Water Resistance
- High Temperature Rating (0-450)
- Extreme Pressure Properties
- Harsh Environment Capabilities
- Anti-Wear Protection
- Corrosion Protection