

CLEAR KOTE TEFLON® BASED CABLE & GEAR LUBRICANT

CLEAR KOTE is a unique clear cable, chain and gear lubricant designed to disburse an oil-like gel coating. CLEAR KOTE sprays thin and sets up with a thick adhesive consistency producing a heavy duty, high impact grease that continually penetrates, lubricates and protects all treated areas. CLEAR KOTE contains PTFE that remains where it is sprayed. CLEAR KOTE works under tough conditions for long lasting protection that will prolong the life of machinery and tools.

FOR USE ON

- Cables & Chains • Springs
- Overhead Doors • Winches • Open Gears
- Sprockets & Slides • Wire Rope

APPLICATIONS

- Industrial Plants • Oil Rigs • Machine Shops •
Marinas • Construction Sites • Garages
- Electronic Repair Shops

DIRECTIONS

Shake well before using. Point spray tip in the direction of desired area to be lubricated. Saturate all areas for complete lubrication and protection. Use extension tube for difficult to reach areas. Reapply as required by working conditions. To clean the tip, invert can and spray to clear.

DANGER / PELIGRO:

Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to Nervous system through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. --No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. If exposed or concerned: Get medical advice or attention. Do not breathe fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep

EXCLUSIVELY FOR INDUSTRIAL & INSTITUTIONAL USE



CLEAR KOTE

Teflon® Based Cable & Gear Lubricant

- *Withstands High Pressure Loads*
- *Triple Action: Protects, Penetrates & Lubricates*
- *Extreme Temperature Resistance—Up to 600°F*
- *No Chlorinated Solvents*
- *Long Lasting—Extremely Durable*
- *Sprays Thin—Sets Up Like a High Impact Grease*

NET WT.
14 OZ.

DANGER/PELIGRO

FLAMMABLE AEROSOL. CONTAINS GAS UNDER
PRESSURE; MAY EXPLODE IF HEATED.
AEROSOL INFLAMABLE. CONTIENE GAS A PRESIÓN;
PUEDE EXPLOTAR SI SE CALIENTA.

comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Store locked up. Dispose of contents and container in accordance with local, state, and national regulations.



Aerosol Inflammable. Contiene gas a presión; Puede explotar si se calienta. Causa irritación de la piel y ocular. Se sospecha que perjudica la fertilidad o el feto. Puede causar somnolencia o mareos. Puede causar daños al sistema nervioso través de la exposición prolongada o repetida. Puede ser fatal en caso de ingestión y entra por las vías respiratorias.

Mantenga lejos de calor, chispas, llamas abiertas, y superficies calientes. --No Fumar. No pulverice en llamas abiertas u otra fuente de ignición. Envase presurizado: No perforo ni queme, incluso después de usar. Proteja de la luz solar. No exponga a temperaturas que excedan 50°C/122°F. Almacene en un lugar bien-ventilada. Lávese bien las manos después de manipular. Use guantes protectores y protección para los ojos. Si en la piel: Lave con bastante agua. Si irritación en la piel ocurre: Obtenga atención médica. Remueva la ropa contaminada lávela antes de utilizar. Si cae en los ojos; Enjuague cuidadosamente con agua durante varios minutos. Remueva lentes de contacto, si están presentes y fáciles de remover. Continúe enjuagando. Si persiste la irritación ocular: Consulte con un medico. Obtenga instrucciones especiales antes de utilizar. No manipule antes de haber leído y comprendido todas las precauciones de seguridad. Si ha sido expuesto o preocupado: obtenga atención médica. No respire los humos, la niebla, vapores, o el rocío. Utilice solamente afueras o en áreas bien-ventiladas. Si en inhalado: Remueva la persona al aire fresco y mantenga cómoda para respirar. Llame al centro de envenenamiento o un doctor si se siente mal. Si se ingiere: Llame inmediatamente a un centro de control de venenos. NO induzca vomito. Almacene bajo llaves. Elimine el contenido y envase de acuerdo con las ordenanzas locales, estatales, y reglamentos nacionales. No respire los humos, la niebla, vapores, o el rocío.

Teflon® is a registered trademark of E.I. Du Pont.

HMS CODES: Health – 1; Flammability – 3; Reactivity – 0; Personal – B

Made in USA

Product Code: 7205-A
To Reorder Call (281) 647-9700
or 1-800-295-BETA

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
P.O. BOX 218686
HOUSTON, TX 77218