

(281) 647-9700 or 1-800-295-BETA Product Code: 2002-P

L.T. RED-X

Odorless Industrial Line Treatment

 NON-FUMING • USE IN PUBLIC AREAS
SAFE FOR USE IN TOILETS, URINALS, SEPTIC SYSTEMS, MOST PIPES, FIXTURES AND PLUMBING
• FAST ACTING FORMULA

GREAT FOR USE IN

- FLOOR DRAINS URINALS TOILETS •
- SINKS SEPTIC SYSTEMS SLOW MOVING DRAINS
 - COMPLETELY STOPPED UP DRAINS TUBS •

DIRECTIONS

Ready to use formulation.

Preventative Maintenance: Use 1/4 cup of L.T. RED-X with 1 cup of hot water. Pour in drain. For larger drains, mix 1/2 cup of L.T. RED-X with 2 cups of hot water. Do not use the drain for 5 minutes.

Stopped Up Drains: Remove Standing water and pour 1/2 cup of L.T. RED-X in the drain. Add 1 cup hot water. For larger drains, use 3/4 cup of L.T. RED-X in the drain with 2 cups of hot water. Do not use drain for 10 minutes. (If necessary use plunger to assist process.) Urinals, Toilets & Tubs: Pour 3/4 cup of L.T. RED-X and add 4 cups of hot water. Let stand for 1/2 hour before flushing. (If necessary use plunger to assist the process.)

CAUTION: Do not use where acid drain openers are present.

BETA DATA

FLASH POINT:	None	WETTING ABILITY:	N/A
VISCOSITY:	Thick	BOILING POINT: >23	39°F
COLOR:	Red	SOLUBILITY IN WATER: 10	00%
SPECIFIC GRAVITY:	1.38	PHOSPHATES: N	lone
TOXICITY:	2 mg / m ³	BIODEGRADABILITY:	No
DETERGENCY:	N/A	pH:	12
STORAGE STABILITY:	1 year +	% VOLATILE BY VOLUME:	50
COLD STABILITY:	32°F	EVAPORATION RATE:	N/A
ODOR:	None	FORM: Viscous Lie	quid

BETA TECHNOLOGY, INC. CORPORATE HEADQUARTERS HOUSTON, TX 77218