



BETA-50

DIELECTRIC SAFETY DEGREASER

- USDA AUTHORIZED
- ZERO FLASH POINT
- NON FILMING
- 29,000 VOLT DIELECTRIC STRENGTH
- CONTROLLED EVAPORATION
- INSTANTLY ATTACKS GREASE

FOR USE IN

- INDUSTRIAL PLANTS
- HOSPITALS
- SCHOOL DISTRICTS
- MACHINE SHOPS
- MUNICIPALITIES
- OFFICE BUILDINGS
- CONSTRUCTION COMPANIES
- OIL RIGS
- NURSING HOMES

DIRECTIONS

Brush or spray onto the surface to be cleaned or use in a vat for immersion cleaning. No special rinsing or flushing is necessary, although if desired, surfaces may be flushed with fresh solvent. Use without dilution and without heat. Repeat application if necessary for heavily encrusted soils.

FOR IMMERSION: Immerse for three to five minutes. Avoid prolonged immersion, as it could damage varnish, rubber or plastic parts. Use instead of carbon tetrachloride, kerosene, 1,1,1 trichloroethane, naphtha or other flammable solvents. When contaminated with soil, do not discard, just filter out the foreign matter and use it over again. Keep vat covered to avoid evaporation.

BETA DATA

FLASH POINT:	None	WETTING ABILITY:	Saturates
VISCOSITY:	Thin	BOILING POINT:	185° F
COLOR:	Clear	SOLUBILITY IN WATER:	0%
SPECIFIC GRAVITY:	1.45	PHOSPHATES:	None
TOXICITY:	50 ppm OSHA TLV	BIODEGRADABILITY:	No
DETERGENCY:	N/A	pH:	N/A
STORAGE STABILITY:	1 year +	% VOLATILE BY VOLUME:	100
COLD STABILITY:	0° F	EVAPORATION RATE:	Moderate
ODOR:	Chlorinated Solvent	FORM:	Solvent Base Liquid

BETA TECHNOLOGY
CORPORATE HEADQUARTERS
HOUSTON, TX 77084