



TO REORDER CALL:
(281) 647-9700
or
1-800-295-BETA

Product Code:
2072-A

RC 1000

SPRAY RUBBERIZED COATING

RC 1000 is a specialized rubberized coating that can be used for literally thousands of different applications. Use this product virtually anywhere on almost any type of surface such as metal, stainless steel, tin, cement, wood, etc. This is great for sealing out moisture and sound.

- REMAINS PLIABLE FOR A VARIETY OF APPLICATIONS • RESISTS CORROSION FROM SALT
- SEALS OUT MOISTURE • RESISTS CRACKING AND FREEZING
- RESISTS PEELING AND DRIPPING • SEALS OUT SOUND • PAINTABLE
- RESISTS ABRASION • FLEXIBLE • PREVENTS RUST
- RESISTS FREEZING IN THE COLD

FOR USE ON

- COATING CONDENSATE PANS • AIR DUCT SEALER • GUTTER AND FLASHING SEALER
- UNDERBODY SOUND DEADENER • ROOF PATCH SEALER • PINPOINT LEAK SEALER
- UNDERBODY CORROSION PREVENTER • CRACK SEALER FOR DRIVEWAYS
- POST AND WOOD PRESERVER • TREE WOUND DRESSING • NUT & BOLT SEALER
- INSULATE AND BUNDLE ELECTRICAL WIRES • RESISTS FREEZING IN THE COLD

DIRECTIONS

SHAKE CAN BEFORE USING. Clean surface of dirt and rust. Hold RC 1000 12 inches from surface. Spray a thin coat. Build-up desired thickness. Read MSDS before using. Wipe up overspray by spraying BETA-52 or GREASE AWAY on a cloth and clean up as needed. NOTE: After each use, invert can and apply a short burst to clear actuator.

BETA DATA

FLASH POINT:	-156 °F (-104.4 °C)	SOLUBILITY IN WATER:	None
COLOR:	Black	ODOR:	Solvent
PROPELLANT:	Liquefied Petroleum Gas	BIODEGRADABILITY:	N/A
STORAGE STABILITY:	1 yr. +	EVAPORATION RATE:	N/D
SPECIFIC GRAVITY:	0.8768	FORM:	Aerosol
COLD STABILITY:	Excellent	% VOLATILE BY VOLUME:	N/D

BETA TECHNOLOGY, INC.

CORPORATE HEADQUARTERS

P.O. Box 218686 • Houston, TX 77218-8686