



(281) 647-9700
or 1-800-295-BETA

Product Code: 2150

A.S.L.-2200™

GRAPHITE BASED ANTI-SEIZE LUBRICANT

- EXTREME PRESSURE SAFE • SEALS AND LUBRICATES
- PREVENTS SEIZING, GALLING OR FRETTING
- COMPLETELY IMPERVIOUS TO WATER • NON-MELT FORMULA
- INDUSTRIAL TEMPERATURE RATINGS FROM -30° TO 2200°F+

FOR USE ON:

- BOLTS • NUTS • PRESS FIT UNIONS • BUSHINGS • GASKETS •
- SCREWS • SPARK PLUGS • VALVES • STAINLESS STEEL • NICKEL •
- FERROUS & NON FERROUS METALS • MANIFOLDS •
- PIPE THREADS • FLANGES • THREADED FITTINGS • CASTINGS •
- FORMING DIES • PACKING UNIONS • LUG NUTS • THREAD BOLTS •
- DRIVE CHAINS • PULLEYS • FUEL INJECTORS • JIBS •
- HYDRAULIC FITTINGS • SHAFTS • WORM GEARS • ROLLER ASSEMBLIES •
- CASTERS • STUD BOLTS • THRUST, PLAIN & SLIDE BEARINGS •
- PUMP SUB ASSEMBLIES • "U" JOINT BEARINGS • BATTERY TERMINALS •
- PITCH ADJUSTER ON PLOWS • ETC. •

DIRECTIONS:

Clean surface with Beta-52 thoroughly. Brush on a complete coating over the surface. Complete assembly and wipe off the excess material. NLGI Rating #2.

BETA DATA

| | |
|---------------------|---------------|
| FLASH POINT: | None |
| BOILING POINT: | 532°F |
| COLOR: | Sliver-Gray |
| SPECIFIC GRAVITY: | 1.02 |
| TOXICITY: | Non-Hazardous |
| DETERGENCY: | N/A |
| STORAGE STABILITY: | 1 year + |
| COLD STABILITY: | 0°F |
| ODOR: | N/A |
| LEAD CONCENTRATION: | None |

| | |
|-----------------------|-------------|
| WETTING ABILITY: | N/A |
| VISCOSITY: | Very Thick |
| SOLUBILITY IN WATER: | 0% |
| PHOSPHATES: | None |
| BIODEGRADABILITY: | No |
| pH: | N/A |
| % VOLATILE BY VOLUME: | 0 |
| EVAPORATION RATE: | Slow |
| FORM: | Thick Paste |

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218