



(281) 647-9700
or 1-800-295-BETA

Product Code: 2250-A

METAL KOTE



CLEAR COAT PROTECTANT Film

- PREVENTS CORROSION • PAINTABLE • FLEXIBLE • NON-CRACK OR PEEL FORMULA
- WELDABLE • USDA AUTHORIZED • MIL SPEC GRADE • INDOOR/OUTDOOR USE

GREAT FOR USE ON:

Castings
Valves
Tools

Pipe
Hoists
Winches

Cables
Threads
Rigging

dies
Housing
Pulleys

Stamped Metal Parts.

DIRECTIONS:

Clean parts of any dirt, soil, rust or scale prior to applying Metal Kote. Shake the can well prior to spraying. Hold can 8 to 10 inches away from application point. Apply in a slow, steady sweeping spray. Saturate surface completely with product. For ultra harsh environments, apply a second coat after 5 minutes.

Total set up and cure time – two hours. When coating is hard, it is ready to be handled.

Coating Thickness

2 & 3 mil
5 & 6 mil

Outdoor Storage

1 year
2 years

Indoor Storage

Indefinite
Indefinite

To remove coating, wash treated part with Beta-52. Once cleaned, parts are ready to be painted.

BETA DATA

FORM: Solvent Based Aerosol
ODOR: Petroleum Solvent
COLOR: Amber
DETERGENCY: N/A
TOXICITY: 500 ppm OSHA TLV
WETTING ABILITY: Good
PHOSPHATES: N/A
STORAGE STABILITY: 1 year +
COLD STABILITY: 0°F

FLASH POINT: 150°F TCC
FLAME EXTENSION: 15"
SOLUBILITY IN WATER: 0%
SPECIFIC GRAVITY: 0.76
% VOLATILE BY VOLUME: 40%
EVAPORATION RATE: Fast
BIODEGRADABLE: Yes
PROPELLANT: Hydrocarbon
pH: N/A

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218