




To Reorder Call (281) 647-9700  
or 1-800-295-BETA

Product Code:  
2562-A



# PRO-VOLT ELECTRICAL WATERPROOFING Spray

- Dries Clear • Flexible • Fast Drying
- Improves Dielectric Protection • Enhances Conductivity
- Protects Against Corrosion • Creates Moisture Shield
- All-Weather Protection

## GREAT FOR USE ON

- Electrical Boxes • Circuit Boards • Wiring • Cable Connections
- Junction Boxes • Electrical Panels • Exposed Contacts
- Conduit Joints • Lighting • Motors, etc.

## DIRECTIONS

Remove plastic cap. Shake can for 30 to 40 seconds. Surface should be clean and dry before application. Spray in short sweeping strokes until desired coverage is achieved. Allow surface to dry for 15 minutes before use. To improve above 300 volt dielectric protection (4 milwatt), additional applications can be made. Clean up with solvent. Turn can upside down after use and spray to clear nozzle. Do not apply to energized equipment or live high voltage connections.

## BETA DATA

FORM:	Solvent Based Aerosol	FLASH POINT:	>100°F
ODOR:	Moderate Solvent	FLAME EXTENSION:	<18"
COLOR:	Clear	SOLUBILITY IN WATER:	N/A
DETERGENCY:	N/A	SPECIFIC GRAVITY:	0.77
TOXICITY:	100 ppm OSHA PEL	% VOLATILE BY VOLUME:	N/A
WETTING ABILITY:	N/A	EVAPORATION RATE:	Medium Fast
PHOSPHATES:	N/A	BIODEGRADABLE:	N/A
STORAGE STABILITY:	1 year +	PROPELLANT:	Hydrocarbon
COLD STABILITY:	32°F	pH:	N/A

**BETA TECHNOLOGY**  
**CORPORATE HEADQUARTERS**  
**HOUSTON, TX 77084**