



To Reorder Call (281) 647-9700
or 1-800-295-BETA

Product Code: 2565-A

GEN PEN™

GENERAL PURPOSE LUBRICANT

- RELEASES RUSTED NUTS & BOLTS •
- PROTECTS AGAINST FUTURE CORROSION •
- LEAVES A RESIDUAL MOLECULAR SHIELD •
- BREAKS UP GREASE, TAR, SCALE & SLUDGE •
- DEFENDS AGAINST MOISTURE DAMAGE •

GREAT FOR USE ON

ENGINE BOLTS	PIPE THREADS	SHAFTS	HINGES
NUTS & SCREWS	WHEEL STUDS	SLIDES	LEVERS
ENGINE FITTINGS	“O” RINGS	VALVES	OUTDOOR/INDOOR LOCKS
BRAKE PARTS	DIE BOLTS	CASTERS	BOILER ASSEMBLIES
A/C PARTS	HEAT RISERS	ROLLERS	CYLINDER HEAD STUDS
CAP SCREWS	BALL BEARINGS	SPROCKETS	EXHAUST SYSTEM PARTS
SHACKLE PINS	SHOCK MOUNT BOLTS	“U” JOINTS	

DIRECTIONS

REGULAR USE: Shake the can well before using. Spray area well until completely saturated. Allow GEN PEN to activate for a couple of minutes.

IN CASE OF EXTREME CORROSION: Re-apply as soon as the first sign of relief is noticed, and continue to disassemble.

BETA DATA

FLASH POINT:	110° F TCC	WETTING ABILITY:	Saturates
PROPELLANT:	Hydrocarbon	FLAME EXTENSION:	18"
COLOR:	Brown	SOLUBILITY IN WATER:	0%
SPECIFIC GRAVITY:	0.83	PHOSPHATES:	None
TOXICITY:	400 ppm OSHA TLV	BIODEGRADABILITY:	None
DETERGENCY:	None	pH:	N/A
STORAGE STABILITY:	1 year +	% VOLATILE BY VOLUME:	20%
COLD STABILITY:	0° F	EVAPORATION RATE:	Slow
ODOR:	Strong Solvent	FORM:	Solvent Base Aerosol

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218