



To Reorder Call (281) 647-9700
or 1-800-295-BETA

Product Code: 2580-A

CABLELOCITY™

O.G.

Cable, Chain & Open Gear Lubricant

- Eliminates Friction • Heavy Load Protection • Repels Moisture •
- Guards Against Rust • Withstands Extreme Pressure • Provides Total Saturation •
- Minimizes Dust Attraction • Sprays Thin – Sets Thick •
- Fortified with Unique Adhesive and Cohesive Agents •

FOR USE ON

- CABLE • CHAIN • WIRE ROPE • DRAG LINES •
- OPEN GEARS • SPROCKETS • SLIDES • WINCHES •

GREAT FOR

- CEMENT MILLS • COMMERCIAL LAUNDRIES • TRANSPORTATION DEPT. •
- CONSTRUCTION COMPANIES • FOUNDRIES • MACHINE SHOPS •
- ASPHALT PLANTS • MANUFACTURING PLANTS • ROLLING STOCK •
- SAW MILLS • TRUCKING COMPANIES • INDUSTRIAL PLANTS •
- METAL FABRICATORS • OFFSHORE OPERATORS • OIL FIELD SVC COMPANIES •
- WASTE TREATING PLANTS • DREDGING COMPANIES • PORT SVC COMPANIES •

DIRECTIONS

Shake well before using. Hold at least 6" from surface to be lubricated. Initially spray an even coating. Start up equipment and run to transfer product over all operating surfaces. Spray a light second coat to assure complete coverage. Reapply as required by working conditions.

BETA DATA

FLASH POINT:	>73°F TCC	WETTING ABILITY:	Saturates
FLAME EXTENSION:	18"	PROPELLANT:	Hydrocarbon
COLOR:	Black	SOLUBILITY IN WATER:	0%
SPECIFIC GRAVITY:	0.82	PHOSPHATES:	None
TOXICITY:	400 ppm OSHA TLV	BIODEGRADABILITY:	No
DETERGENCY:	None	pH:	N/A
STORAGE STABILITY:	1 Yr +	% VOLATILE BY VOLUME:	43.5%
COLD STABILITY:	0° F	EVAPORATION RATE:	Slow
ODOR:	Petroleum Solvent	FORM:	Solvent Base Aerosol

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218