



(281) 647-9700
or 1-800-295-BETA

Product Code: 2627-A

KOOL BURN



- EVAPORATES AFTER USE
- PREVENTS WELD SPATTER FROM STICKING
- PROTECTS SURROUNDING EQUIPMENT FROM TORCH DAMAGE
- BIODEGRADABLE & NON-TOXIC • NON-CORROSIVE GEL FORMULATION

IDEAL FOR THESE APPLICATIONS

- WELDING • BRAZING • SOLDERING

GREAT FOR PROTECTION OF

- PLASTICS • FITTINGS • SHEETROCK • INSULATION • WIRING • WOODWORK

DIRECTIONS

TO BLOCK HEAT TRANSFER: Apply KOOL BURN on and around work surfaces to help prevent damage while welding, brazing or soldering

TO USE AS AN ANTI-SPATTER ON WORK SURFACE AREAS: Apply KOOL BURN on the work surface to be welded. KOOL BURN will evaporate after use. Brush or wipe area clean if a faster clean-up is needed.

BETA DATA

FLASH POINT:	None	WETTING ABILITY:	Saturates
PROPELLANT:	Nitrogen	FLAME EXTENSION:	None
COLOR:	White Gel	SOLUBILITY IN WATER:	100%
SPECIFIC GRAVITY:	1.00	PHOSPHATES:	None
TOXICITY:	Non-hazardous	BIODEGRADABILITY:	Yes
DETERGENCY:	Low	pH:	10.5
STORAGE STABILITY:	1 year +	% VOLATILE BY VOLUME:	100
COLD STABILITY:	32°F	EVAPORATION RATE:	Slow
ODOR:	None	FORM:	Water Based Aerosol

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218