

(281) 647-9700 or 1-800-295-BETA **Product Code: 2640-A**

REMOVE

GEL

Paint, Varnish, Graffiti Remover

- USDA AUTHORIZED
 NON-FLAMMABLE
 CLINGS TO VERTICAL SURFACES
- SAFE ON METAL, BRICK, TILE & CERAMIC SURFACES

FOR USE IN

- FACTORIES PAINT SHOPS HOSPITALS •
- MUNICIPALITIES APARTMENTS HOUSING AUTHORITIES
 - GARAGES
 SCHOOL DISTRICTS

DIRECTIONS

Shake well before using. Holding can eight to ten inches from surface to be treated, apply a medium to heavy coat on surface as needed. A thicker application will speed up action. Blistering will occur in three or four minutes, but may take up to twenty minutes, depending on material being treated. Allow product to complete blistering before removing.

BETA DATA

FLASH POINT: None PROPELLANT: Hydrocarbon COLOR: Clear **SPECIFIC GRAVITY:** 1.20 TOXICITY: 25 ppm OSHA TLV **DETERGENCY:** Excellent STORAGE STABILITY: 1 year + 0° F COLD STABILITY: ODOR: **Chlorinated Solvent** **WETTING ABILITY:** Excellent FLAME EXTENSION: None 15% **SOLUBILITY IN WATER:** PHOSPHATES: None **BIODEGRADABILITY:** No N/A :Ha 97+ % VOLATILE BY VOLUME: Medium **EVAPORATION RATE:** FORM: Solvent Base Aerosol

BETA TECHNOLOGY, INC. CORPORATE HEADQUARTERS HOUSTON, TX 77218