



To Reorder Call (281) 647-9700
or 1-800-295-BETA

Product Code: 2880-A

KOOL TOOL

FOAMING PENETRATING & CUTTING OIL

FOR USE IN

- INDUSTRIAL MACHINERY • MACHINE SHOPS •
- HOMES • CARS • TRUCKS • OIL RIGS • HOTELS •

DIRECTIONS

Remove protective cap. Point opening in desired direction. Hold container 6-12 inches from surface to be treated. Press button to spray. Spray liberally. Reapply periodically as required.

BETA DATA

FLASH POINT:	+200°F TCC	WETTING ABILITY:	Saturates
FLAME EXTENSION:	18"+	PROPELLANT:	Hydrocarbon
COLOR:	Straw Colored	SOLUBILITY IN WATER:	0%
SPECIFIC GRAVITY:	0.92	PHOSPHATES:	None
TOXICITY:	100 ppm OSHA TLV	BIODEGRADABILITY:	No
DETERGENCY:	None	pH:	N/A
STORAGE STABILITY:	1 year +	% VOLATILE BY VOLUME:	26
COLD STABILITY:	0° F	EVAPORATION RATE:	Slow
ODOR:	Mild Petroleum	FORM:	Oil Base Aerosol

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218