



(281) 647-9700
or 1-800-295-BETA

Product Code: 7200-A

BETA-LUBE

Moly-Disulfide Lubricant

- USDA AUTHORIZED • ZERO FLASH POINT • DRY FILM
- OPERATING RANGE FROM -40°F TO +600°F • NO RUN OFF
- FAST DRYING • ADHERES TO METAL

FOR USE IN

- CONSTRUCTION AREAS • PIPE YARDS • HEAVY EQUIPMENT •
- OIL RIGS • INDUSTRIAL PLANTS • MACHINES SHOPS •
- GARAGES •

DIRECTIONS

Shake can well before using. Clean surface thoroughly. Hold can 6 to 8 inches from surface and apply evenly. Thin coats are preferable. Allow 1 to 5 minutes for adequate drying. The concentration of solids in this product may clog nozzle. Shake vigorously and often. Before storing, turn can upside-down and spray until clear.

BETA DATA

FLASH POINT:	None	WETTING ABILITY:	None
PROPELLANT:	Hydrocarbon	FLAME EXTENSION:	12"
COLOR:	Charcoal Gray	SOLUBILITY IN WATER:	0%
SPECIFIC GRAVITY:	1.27	PHOSPHATES:	None
TOXICITY:	25 ppm OSHA TLV	BIODEGRADABILITY:	No
DETERGENCY:	None	pH:	N/A
STORAGE STABILITY:	1 year	% VOLATILE BY VOLUME:	94
COLD STABILITY:	0°F	EVAPORATION RATE:	Slow
ODOR:	Mild Sweet	FORM:	Solvent Base Aerosol

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218