



(281) 647-9700
or 1-800-295-BETA

Product Code: 7205-A

CLEAR KOTE

Teflon[®] Based Cable & Gear Lubricant

- WITHSTANDS HIGH PRESSURE LOADS
- TRIPLE ACTION: PROTECTS, PENETRATES & LUBRICATES
- EXTREME TEMPERATURE RESISTANCE—UP TO 600°F
- NO CHLORINATED SOLVENTS • LONG LASTING—EXTREMELY DURABLE
- SPRAYS THIN—SETS UP LIKE A HIGH IMPACT GREASE

GREAT FOR USE ON

- CABLES & CHAINS • SPRINGS • OVERHEAD DOORS • WINCHES
- OPEN GEARS • SPROCKETS & SLIDES • WIRE ROPE

APPLICATIONS

- INDUSTRIAL PLANTS • OIL RIGS • MACHINE SHOPS • MARINAS
- CONSTRUCTION SITES • GARAGES • ELECTRONIC REPAIR SHOPS

DIRECTIONS

Shake well before using. Point spray tip in the direction of desired area to be lubricated. Saturate all areas for complete lubrication and protection. Use extension tube for difficult to reach areas. Reapply as required by working conditions. To clean the tip, invert can and spray to clear.

BETA DATA

| | | | |
|---------------------------|--------------------------|------------------------------|-----------------------|
| FLASH POINT: | <100°F TCC | WETTING ABILITY: | None |
| PROPELLANT: | Hydrocarbon | FLAME EXTENSION: | 18" |
| COLOR: | Hazy, Tan, Gelled Liquid | SOLUBILITY IN WATER: | 0% |
| SPECIFIC GRAVITY: | 0.83 | PHOSPHATES: | None |
| TOXICITY: | 400 ppm OSHA PEL | BIODEGRADABILITY: | No |
| DETERGENCY: | N/A | pH: | N/A |
| STORAGE STABILITY: | 1 year + | % VOLATILE BY VOLUME: | 49.8% |
| COLD STABILITY: | 32°F | EVAPORATION RATE: | <1 |
| ODOR: | Acetate | FORM: | Solvent Based Aerosol |

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218