



(281) 647-9700
or 1-800-295-BETA

Product Code: 7210-A

B-LUBE (MCF)

ENVIRONMENTALLY FRIENDLY

Moly-Disulfide LUBRICANT

- USDA AUTHORIZED • ZERO FLASH POINT • DRY FILM
- OPERATING RANGE FROM -40°F TO +600°F • NO RUN OFF
- FAST DRYING • ADHERES TO METAL

FOR USE IN

- CONSTRUCTION AREAS • PIPE YARDS • HEAVY EQUIPMENT •
- OIL RIGS • INDUSTRIAL PLANTS • MACHINES SHOPS •
- GARAGES •

DIRECTIONS

Shake well before using. Apply a thin coat of B-LUBE (MCF) to the surface with a smooth sweeping spray. Allow B-LUBE (MCF) to cure for 30 minutes before exposing to water/rain. Dry time is 1–3 minutes. Excessive or thick coating will decrease the efficiency of B-LUBE (MCF). Before storing unused product, turn can upside-down and spray nozzle until clear.

BETA DATA

FLASH POINT:	N/A	WETTING ABILITY:	None
PROPELLANT:	Hydrocarbon	FLAME EXTENSION:	>18"
COLOR:	Dark Gray	SOLUBILITY IN WATER:	Partial
SPECIFIC GRAVITY:	0.83	PHOSPHATES:	N/A
TOXICITY:	100 ppm OSHA PEL	BIODEGRADABILITY:	No
DETERGENCY:	N/A	pH:	N/A
STORAGE STABILITY:	1 year +	% VOLATILE BY VOLUME:	>90
COLD STABILITY:	0°F	EVAPORATION RATE:	Fast
ODOR:	Solvent	FORM:	Solvent-Based Aerosol

BETA TECHNOLOGY, INC.
CORPORATE HEADQUARTERS
HOUSTON, TX 77218